## NSN 5910-01-190-4606

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-190-4606

Rody	Style:
Roav	Style:

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

**Dummy Terminal Quantity:** 

111

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.250 inches 0.250 inches 0.250 inches

**Body Diameter:** 

1.010 inches

**Body Length:** 

3.640 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.400 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

2.0

**Electrical Polarization:** 

Polarized

**End Application:** 

Modem, digital data md-1131/g

**Capacitance Value Per Section:** 

220.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+100.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.346

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-190-4606

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:	
Plastic	
Terminal Type And Quantity:	
2 uninsulated wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A010b0