NSN 5910-01-190-6660

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-190-6660 **Body Style:** W/o mtg facilities, terminal (s) on one surface Reliability Indicator: Not established **Terminal Length:** 0.500 inches **Body Length:** 2.160 inches **Body Width:** 1.310 inches **Body Height:** 2.000 inches Center To Center Distance Between Terminals Parallel To Length: 0.812 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **End Application:** 4940-01-052-3773 shop equipment, battery servicing, shelter mounted **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 660.0 ac-rms single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 10000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.2000 **Terminal Surface Treatment:** Solder

Dielectric Material: Paper and plastic **Terminal Type And Quantity:** 2 quick disconnect, male, four blade Shelf Life: N/a

NSN 5910-01-190-6660

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0