## NSN 5910-01-190-6699

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-190-6699

| Body Style:         |                      |
|---------------------|----------------------|
| W/o mtg facilities, | axial terminalsw/o m |

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.500 inches 1.500 inches 1.500 inches

**Body Diameter:** 

0.110 inches

**Body Length:** 

0.290 inches

**Terminal Diameter:** 

0.020 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**End Application:** 

6625-01-144-4481 test set, radio

**Capacitance Value Per Section:** 

4.700 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic

**Capacitive Electrode Material:** 

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:** 

4.000

Dc Leakage At Reference Temp:

1.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-190-6699

Electrolytic Fixed Capacitor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0