

View Online at <https://aerobasegroup.com/nsn/5910-01-190-7560>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.375 inches

Body Diameter:

0.100 inches

Body Length:

0.170 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

4920-01-111-2981 automatic test; forrestal class cv; ticonderoga class cg (47); sturgeon class ssn (637); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); spruance class dd (963); landing craft air cushion (lcac); support equipment, b-1 aircraft; los angeles class ssn (688); virgina class cgn (41)

Capacitance Value Per Section:

15.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0