

View Online at <https://aerobasegroup.com/nsn/5910-01-190-9147>

Thread Class:

2a

Body Style:

Piston

Terminal Length:

1.500 inches

Bushing Diameter:

0.257 inches

First Flat Length:

0.125 inches single shaft

Shaft Diameter:

0.125 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.781 inches single shaft

Body Length:

Between 0.688 inches and 0.750 inches

Overall Diameter:

0.312 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Terminal Diameter:

0.025 inches

Quality Factor At 25 Deg Celsius:

500.0

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Bushing Width:

0.237 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, parallel flatted single shaft

Capacitance Range In Picofarads:

+0.8/+14.0 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 shaft

Capacitance Drift In Picofarads:

0.04 single section

Material:

Glass capacitive electrode

Terminal Type And Quantity:

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0