

View Online at https://aerobasegroup.com/nsn/5910-01-191-5300

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

## **Body Diameter:**

0.562 inches

**Body Length:** 

1.562 inches

**Terminal Diameter:** 

0.032 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

0.470 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

#### **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-18312/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-01-191-5300 Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



**Fiig:** A010b0