NSN 5910-01-191-9831

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-191-9831 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.600 inches 1.600 inches |
| Body Diameter: |
| 0.197 inches |
| Body Length: |
| 0.492 inches |
| Terminal Diameter: |
| 0.024 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 4.700 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 63.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 4.00 |
| Dc Leakage At Reference Temp: |
| 6.000 microamperes |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-191-9831

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0