# NSN 5910-01-191-9833

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-191-9833

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not establishednot established

# **Terminal Length:**

1.600 inches 1.600 inches 1.600 inches

**Body Diameter:** 

0.200 inches

**Body Length:** 

0.500 inches

**Terminal Diameter:** 

0.020 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

#### **Anode Type:**

Plain foil

### **Impedance At Minimum Operating Tempurature In Ohms:**

2.0

#### **Electrical Polarization:**

Polarized

# **Capacitance Value Per Section:**

2.200 microfarads single section

# **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

63.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

Case Material:

Metal

# **Capacitive Electrode Material:**

Aluminum

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.1000

### **Equivalent Series Resistance At Reference Tempurature In Ohms:**

60.31

## Dc Leakage At Reference Temp:

4.000 microamperes

# **Terminal Surface Treatment:**

Solder

#### **Case Insulation Material:**

Plastic

# NSN 5910-01-191-9833

Electrolytic Fixed Capacitor - Page 2 of 2



Γerminal Type And Qι	uantity:
----------------------	----------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0