NSN 5910-01-191-9834

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/psp/5010_01_101_0834

| View Online at https://aerobasegroup.com/nsn/5910-01-191-9834 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.750 inches |
| Body Diameter: |
| 0.375 inches |
| Body Length: |
| 0.750 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| 6625-01-144-4481 test set radio |
| Capacitance Value Per Section: |
| 0.220 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section |
| |
| 300.0 dc single section |
| 300.0 dc single section Tolerance Range Per Section: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Surface Treatment: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Surface Treatment: Solder |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Surface Treatment: Solder Terminal Type And Quantity: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: |
| 300.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a |

No

Fiig: A010b0