

View Online at <https://aerobasegroup.com/nsn/5910-01-192-5160>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0100

Terminal Length:

1.250 inches

Body Diameter:

Between 0.080 inches and 0.100 inches

Body Length:

Between 0.150 inches and 0.170 inches

Terminal Diameter:

Between 0.017 inches and 0.021 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

22.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

2.5000

Test Data Document:

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39014/05 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0