

View Online at <https://aerobasegroup.com/nsn/5910-01-192-8879>

**Body Style:**

Dual inlinedual inline

**Reliability Indicator:**

Not establishednot established

**Terminal Length:**

0.120 inches 0.120 inches

**Body Length:**

Between 0.440 inches and 0.460 inches

**Body Width:**

Between 0.240 inches and 0.280 inches

**Body Height:**

0.275 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.300 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.325 inches and 0.375 inches

**Schematic Diagram Designator:**

Two common terminals for each electrode

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Section Quantity:**

2

**Capacitance Value Per Section:**

6.800 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

10.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc all sections

**Tolerance Range Per Section:**

-20.00/+20.00 percent all sections

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.0000

**Dc Leakage At Reference Temp:**

1.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

8 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0