

View Online at <https://aerobasegroup.com/nsn/5910-01-193-3367>

**Body Style:**

W/mtg tabs/flanges, terminals on opposite surfaces

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.000002

**Terminal Length:**

Between 0.612 inches and 0.652 inches

**Body Length:**

Between 3.110 inches and 3.155 inches

**Body Width:**

2.750 inches

**Body Height:**

2.563 inches

**Continuous Current Rating In Amps:**

55.0

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.300 inches and 1.330 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

1.125 inches

**Terminal Diameter:**

0.190 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.745 inches and 1.755 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.748 inches and 1.752 inches

**Schematic Diagram Designator:**

Two common terminals for each electrode

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

4 threaded mounting studs

**Section Quantity:**

2

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

2.850 microfarads 2nd section

**Nonderated Operating Temp:**

Between -18.0 degrees celsius and 63.0 degrees celsius

**Thread Size:**

0.164 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

350.0 ac-rms 2nd section and 200.0 dc 2nd section

**Tolerance Range Per Section:**

-1.00/+1.00 percent 2nd section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.1000

**Case Insulation Material:**

Plastic

**Special Features:**

Impregnated with silicone oil

**Terminal Type And Quantity:**

8 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0