

View Online at <https://aerobasegroup.com/nsn/5910-01-193-3367>

Body Style:

W/mtg tabs/flanges, terminals on opposite surfaces

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.000002

Terminal Length:

Between 0.612 inches and 0.652 inches

Body Length:

Between 3.110 inches and 3.155 inches

Body Width:

2.750 inches

Body Height:

2.563 inches

Continuous Current Rating In Amps:

55.0

Center To Center Distance Between Terminals Parallel To Length:

Between 1.300 inches and 1.330 inches

Center To Center Distance Between Terminals Parallel To Diameter:

1.125 inches

Terminal Diameter:

0.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.745 inches and 1.755 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.748 inches and 1.752 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting studs

Section Quantity:

2

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

2.850 microfarads 2nd section

Nonderated Operating Temp:

Between -18.0 degrees celsius and 63.0 degrees celsius

Thread Size:

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

350.0 ac-rms 2nd section and 200.0 dc 2nd section

Tolerance Range Per Section:

-1.00/+1.00 percent 2nd section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.1000

Case Insulation Material:

Plastic

Special Features:

Impregnated with silicone oil

Terminal Type And Quantity:

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0