

View Online at https://aerobasegroup.com/nsn/5910-01-193-5459

### **Body Style:**

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Length:** 

0.687 inches

**Body Width:** 

Between 0.312 inches and 0.358 inches

**Body Height:** 

Between 0.484 inches and 0.530 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**End Application:** 

Simulator, countermeasures signals an/ulq-13

#### Capacitance Value Per Section:

0.470 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

30000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-01-193-5459 Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



**Fiig:** A010b0