NSN 5910-01-193-7222



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-193-7222 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.500 inches **Body Width:** 0.471 inches **Body Height:** 0.234 inches Center To Center Distance Between Terminals Parallel To Length: 0.400 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **End Application:** Receiving set, countermeasures an/wlq- (v) **Capacitance Value Per Section:** 0.036 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 250000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Surface Treatment:** Solder **Dielectric Material:**

Plastic polyester

Terminal Type And Quantity:
2 uninsulated wire lead

NSN 5910-01-193-7222

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sh	elf	L	ife:
N/	а		

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0