## NSN 5910-01-193-7224

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-193-7224

Body Style:
W/mtg hol (s)/slot(s), terminal(s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.313 inches
Body Length:
2.625 inches
Body Width:
1.000 inches
Body Height:
0.938 inches
Terminal Diameter:
0.164 inches
Unthreaded Mounting Hole Diameter:
0.196 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.125 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
4 threaded mounting holes
Features Provided:
Mounting hardware
Insulation Resistance At Maximum Operating Temp:
2000.0 megohms
Capacitance Value Per Section:
0.010 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.164 inches
Nonderated Continuous Voltage Rating And Type Per Section:
2500.0 dc single section

Feat

**Tolerance Range Per Section:** 

**Criticality Code Justification:** 

-10.00/+10.00 percent single section

NSN 5910-01-193-7224 Plastic Dielectric Fixed Capacitor - Page 2 of 2



Case Material:
Plastic
nsulation Resistance At Reference Temp:
50000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Special Features:
Burn-in test
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
<u> </u>