## NSN 5910-01-193-7230

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-193-7230

D ~ d	Style:
DUUV	Sivie.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.500 inches 1.500 inches 1.500 inches

**Body Diameter:** 

1.385 inches

**Body Length:** 

3.661 inches

**Terminal Diameter:** 

0.040 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

1.6

**Electrical Polarization:** 

Polarized

**End Application:** 

Simulator, countermeasures signals an/ulq-13

**Capacitance Value Per Section:** 

1000.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+100.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

n 24

Dc Leakage At Reference Temp:

2.330 milliamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## NSN 5910-01-193-7230

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type A	and Quantity	<b>/:</b>
-----------------	--------------	-----------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0