

View Online at <https://aerobasegroup.com/nsn/5910-01-193-7233>

**Body Style:**

W/twist tab mtg, terminal (s) on one end/w/twist tab mtg, terminal(s) on one end

**Reliability Indicator:**

Not established/not established

**Terminal Length:**

0.312 inches 0.312 inches

**Body Diameter:**

1.515 inches

**Body Length:**

2.562 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**End Application:**

Simulator, countermeasures signals an/ulq-13

**Capacitance Value Per Section:**

2000.000 microfarads single section

**Nonderated Operating Temp:**

Between -20.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

40.0 dc single section

**Tolerance Range Per Section:**

-10.00/+100.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.67

**Dc Leakage At Reference Temp:**

1.700 milliamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0