

View Online at <https://aerobasegroup.com/nsn/5910-01-193-7233>

Body Style:

W/twist tab mtg, terminal (s) on one end/w/twist tab mtg, terminal(s) on one end

Reliability Indicator:

Not established/not established

Terminal Length:

0.312 inches 0.312 inches

Body Diameter:

1.515 inches

Body Length:

2.562 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Simulator, countermeasures signals an/ulq-13

Capacitance Value Per Section:

2000.000 microfarads single section

Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

40.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.67

Dc Leakage At Reference Temp:

1.700 milliamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0