NSN 5910-01-193-7296

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-193-7296 **Body Style:** Rotary **Terminal Length:** 0.12 millimeters **Body Length:** 5.8 millimeters **Body Width:** 5.0 millimeters **Body Height:** 6.0 millimeters Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -800.0/-200.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.2 millimeters **Quality Factor At 25 Deg Celsius:** 300.0 **Terminal Width:** 0.04 millimeters **Terminal Thickness:** 0.01 millimeters **End Application:** Simulator, countermeasures signals an/ulq-13 **Inclosure Type:** Encased **Adjustment Device Torque:** Between 35.0 centimeter-grams and 200.0 centimeter-grams Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal Capacitance Range In Picofarads: +3.5/+20.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc dielectric withstanding single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a **Unit Of Measure:**

--

NSN 5910-01-193-7296

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0