

View Online at <https://aerobasegroup.com/nsn/5910-01-193-7296>

**Body Style:**

Rotary

**Terminal Length:**

0.12 millimeters

**Body Length:**

5.8 millimeters

**Body Width:**

5.0 millimeters

**Body Height:**

6.0 millimeters

**Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:**

-800.0/-200.0 single section

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.2 millimeters

**Quality Factor At 25 Deg Celsius:**

300.0

**Terminal Width:**

0.04 millimeters

**Terminal Thickness:**

0.01 millimeters

**End Application:**

Simulator, countermeasures signals an/ulq-13

**Inclosure Type:**

Encased

**Adjustment Device Torque:**

Between 35.0 centimeter-grams and 200.0 centimeter-grams

**Insulation Dc Resistance At 25 Deg Celsius:**

100000.0 megohms

**Mounting Facility Type And Quantity:**

2 terminal

**Capacitance Range In Picofarads:**

+3.5/+20.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc dielectric withstanding single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Terminal Type And Quantity:**

2 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A096a0