## NSN 5910-01-194-2287

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-194-2287

<b>Body</b>	Stv	٠ ما
DUUV	OLV.	ıe.

W/o mtg facilities, terminals on opposite surfaces

**Body Length:** 

Between 2.180 inches and 2.220 inches

**Body Width:** 

Between 1.690 inches and 1.760 inches

**Body Height:** 

Between 2.050 inches and 2.090 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.126 inches and 0.131 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

Between 1.920 inches and 1.960 inches

**Electrical Polarization:** 

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.910 inches and 0.950 inches

**End Application:** 

B-1b

**Mounting Facility Type And Quantity:** 

4 unthreaded mounting holes

**Capacitance Value Per Section:** 

1100.000 millifarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Capacitive Electrode Material:** 

**Tantalum** 

**Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

Yes - demil/mli

Fiig:

A010b0