NSN 5910-01-194-3090

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-194-3090 **Body Style:** Rotary **Terminal Length:** 0.085 inches **Body Diameter:** 0.180 inches **Body Height:** 0.085 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 100.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -150.0/+150.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.140 inches **Terminal Width:** 0.020 inches **Terminal Thickness:** 0.004 inches **End Application:** Simulator, countermeasures signals an/ulq-13 Inclosure Type: Encapsulated **Adjustment Device Torque:** Between 0.050 inch-ounces and 1.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -20.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +0.5/+2.5 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 square hole **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a **Unit Of Measure:**

--

NSN 5910-01-194-3090

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0