## NSN 5910-01-195-7234

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-195-7234

**Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.200 inches **Body Width:** 0.200 inches **Body Height:** 0.100 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.200 inches **Terminal Diameter:** Between 0.015 inches and 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 1430-01-184-6768 radar set **Capacitance Value Per Section:** 120.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -80.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 1250.0 megohms **Quality Factor At Reference Temp:** 1000.0000 **Terminal Surface Treatment:** Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-195-7234

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0