Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-195-7348

0.397 inches

Terminal Length:

0.109 inches

Bushing Diameter:

0.234 inches

Bushing Length:

0.196 inches

Body Length:

0.288 inches

Overall Diameter:

0.281 inches

Terminal Diameter:

0.094 inches

Quality Factor At 25 Deg Celsius:

5000.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Torque:

Between 0.500 inch-ounces and 6.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Insulation Dc Resistance At Max Operating Temp:

100000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches



Capacitance Range In Picofarads:

+0.8/+10.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 turret

Specification Data: 81349-mil-c-14409/12 government specification Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0