Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-196-1869

# Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.500 inches

Body Length:

0.420 inches

Body Width:

0.300 inches

**Body Height:** 

#### 0.180 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.300 inches

**Terminal Diameter:** 

0.025 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

#### Insulation Resistance At Maximum Operating Temp:

4000.0 megohm-microfarads

#### **Capacitance Value Per Section:**

0.015 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

40000.0 megohm-microfarads

# **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

### **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0