NSN 5910-01-196-2079

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-196-2079

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.688 inches
Body Width:
0.313 inches
Body Height:
0.500 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Emory s. Land class as; tf40b gas turbine systems; 2m/ate microminiauture automatic test equipment; nimitz class cvn; landing craft air
cushion (Icac); tarawa class Iha
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Criticality Code Justification:
Feat
Tolerance Range Per Section:
-2.00/+2.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
150000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Special Features:
Weapon system essential

N/a

Shelf Life:

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-196-2079

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A010b0