## NSN 5910-01-196-5108

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-196-5108

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
0.375 inches 0.375 inches 0.375 inches
Body Diameter:
0.500 inches
Body Length:
1.165 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.200 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
0.12
Electrical Polarization:
Polarized
Capacitance Value Per Section:
270.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
25.0 dc single section
Tolerance Range Per Section:
-10.00/+100.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:

0.32

Dc Leakage At Reference Temp:

4.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## NSN 5910-01-196-5108

Electrolytic Fixed Capacitor - Page 2 of 2



Ferminal Type And Quai	ntity	:
------------------------	-------	---

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0