NSN 5910-01-197-2553

W/thd bushing mtg, terminals on opposite ends

Body Style:

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-197-2553

| Reliability Indicator: | | | | | |
|---|--|--|--|--|--|
| Not established | | | | | |
| Terminal Length: | | | | | |
| 0.218 inches | | | | | |
| Body Diameter: | | | | | |
| 0.690 inches | | | | | |
| Body Length: | | | | | |
| 0.454 inches | | | | | |
| Schematic Diagram Designator: | | | | | |
| Feedthrough | | | | | |
| Mounting Facility Screw Thread Series Designator: | | | | | |
| Unf | | | | | |
| Mounting Facility Type And Quantity: | | | | | |
| 1 threaded bushing | | | | | |
| Features Provided: | | | | | |
| Hermetically sealed case | | | | | |
| Capacitance Value Per Section: | | | | | |
| 0.330 microfarads single section | | | | | |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: | | | | | |
| -15.0/+15.0 without voltage applied single section | | | | | |
| Nonderated Operating Temp: | | | | | |
| Between -55.0 degrees celsius and 125.0 degrees celsius | | | | | |
| Thread Size: | | | | | |
| 0.312 inches | | | | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | | | | |
| 100.0 dc single section | | | | | |
| Tolerance Range Per Section: | | | | | |
| -0.00/+100.00 percent single section | | | | | |
| Case Material: | | | | | |
| Metal | | | | | |
| Insulation Resistance At Reference Temp: | | | | | |
| 800.0 megohms | | | | | |
| Dissipation Factor At Reference Tempurature In Percent: | | | | | |
| 3.0000 | | | | | |
| Terminal Surface Treatment: | | | | | |
| Solder | | | | | |
| Terminal Type And Quantity: | | | | | |

N/a

2 tab, solder lug

Shelf Life:

NSN 5910-01-197-2553

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0