NSN 5910-01-197-2690

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-197-2690 **Body Style:** Piston **Overall Length:** 2.328 inches **Terminal Length:** 0.500 inches **Body Length:** 2.219 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -50.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -150.0/+150.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 2.218 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.234 inches **Terminal Diameter:** 0.030 inches **Quality Factor At 25 Deg Celsius:** 900.0 **Inclosure Type:** Hermetically sealed **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between 0.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +1.5/+250.0 single section **Nonderated Voltage Rating And Type:** 200.0 dc continuous single section or 400.0 dc dielectric withstanding single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 4 wire lead Shelf Life:

N/a

NSN 5910-01-197-2690

Glass Dielectric Variable Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A096a0