

View Online at <https://aerobasegroup.com/nsn/5910-01-197-8498>

Body Style:

Rotary

Terminal Length:

0.130 inches

Overall Height:

Between 0.280 inches and 0.365 inches

Overall Diameter:

Between 0.360 inches and 0.390 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.300 inches

Terminal Diameter:

Between 0.038 inches and 0.044 inches

Quality Factor At 25 Deg Celsius:

500.0

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 6.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+5.5/+18.0 single section

Nonderated Voltage Rating And Type:

350.0 dc continuous single section or 500.0 dc dielectric withstanding single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50/+2.00 single section and -2.50/+2.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Precious Material And Location:

Terminals and all metal surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0