

View Online at https://aerobasegroup.com/nsn/5910-01-197-9429

Body Style:
Dual inline
Reliability Indicator:
Not established
Unable To Decode:
Unable to decode and unable to decode
Terminal Length:
0.176 inches
Unable To Decode:
Unable to decode and unable to decode
Body Length:
Between 0.787 inches and 0.795 inches
Body Width:
Between 0.290 inches and 0.310 inches
Body Height:
0.135 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.690 inches and 0.710 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.300 inches and 0.400 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Section Quantity:
8
Capacitance Value Per Section:
150.000 picofarads all sections
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 all sections
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc all sections
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 all sections
Tolerance Range Per Section:
-5.00/+5.00 percent all sections
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
2.5000

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



**Terminal Surface Treatment:** 

Solder

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0