NSN 5910-01-198-1714

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-198-1714 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.670 inches **Body Length:** 1.313 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 2000.0 megohms **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 200000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.6000 **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-01-198-1714

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A010b0