## NSN 5910-01-198-2516

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-198-2516

**Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.200 inches **Body Width:** 0.200 inches **Body Height:** 0.125 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.250 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 6625-01-079-4203 generator, signal **Capacitance Value Per Section:** 56.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.1000 **Quality Factor At Reference Temp:** 1000.0000

Solder

**Terminal Surface Treatment:** 

## NSN 5910-01-198-2516

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type A	and Quantity	<b>/</b> :
-----------------	--------------	------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0