NSN 5910-01-199-4376

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-199-4376

| view Offilite at https://acrobasegroup.com/hsh/5510-01-155-4570 | |
|--|--|
| Body Style: | |
| W/o mtg facilities terminal (s) on one surface | |
| Reliability Indicator: | |
| Not established | |
| Terminal Length: | |
| 25.0 millimeters | |
| Body Length: | |
| 3.5 millimeters | |
| Body Width: | |
| 4.0 millimeters | |
| Body Height: | |
| 2.15 millimeters | |
| Center To Center Distance Between Terminals Parallel To Length: | |
| 2.5 millimeters | |
| Terminal Diameter: | |
| 0.6 millimeters | |
| Schematic Diagram Designator: | |
| No common or grounded electrode (s) | |
| End Application: | |
| 6625-01-136-8602 synthesizer, ele | |
| Capacitance Value Per Section: | |
| 22.000 picofarads single section | |
| Nonderated Operating Temp: | |
| Between -25.0 degrees celsius and 85.0 degrees celsius | |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: | |
| 0.0 single section | |
| Nonderated Continuous Voltage Rating And Type Per Section: | |
| 63.0 dc single section | |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: | |
| -30.0/+30.0 single section | |
| Tolerance Range Per Section: | |
| -5.00/+5.00 percent single section | |
| Case Material: | |
| Plastic | |
| Insulation Resistance At Reference Temp: | |
| 1000.0 megohms | |
| Dissipation Factor At Reference Tempurature In Percent: | |
| 0.1500 | |
| Terminal Surface Treatment: | |
| Solder | |
| Terminal Type And Quantity: | |

2 uninsulated wire lead

NSN 5910-01-199-4376

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| She | lf | I if | ρ. |
|-----|-----|------|----|
| ~ | ••• | | • |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0