## NSN 5910-01-200-7783

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-200-7783

Body	Stv	le٠
Bouv	JLV	ıc.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

40.0 millimeters 40.0 millimeters 40.0 millimeters

**Body Diameter:** 

22.5 millimeters

**Body Length:** 

51.5 millimeters

**Terminal Diameter:** 

0.8 millimeters

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

2.0

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

3300.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.071

Dc Leakage At Reference Temp:

4.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## NSN 5910-01-200-7783

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0