## NSN 5910-01-200-7790

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-200-7790

Body	Stv	le٠
Bouv	JLV	ıc.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Dummy Terminal Quantity:** 

111

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.000 inches 1.000 inches 1.000 inches

**Body Diameter:** 

1.010 inches

**Body Length:** 

1.140 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.400 inches

**Terminal Diameter:** 

0.040 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

0.408

**Electrical Polarization:** 

Polarized

**End Application:** 

1520-01-106-9519 helicopter, atta

**Capacitance Value Per Section:** 

33.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+100.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.429

Dc Leakage At Reference Temp:

46.000 microamperes

## NSN 5910-01-200-7790 Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
3 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia·

A010b0