NSN 5910-01-201-2249

Electrolytic Fixed Capacitor - Page 1 of 2



on one end

View Online at https://aerobasegroup.com/nsn/5910-01-201-2249

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s)
Reliability Indicator:
Not establishednot established
Terminal Length:
0.250 inches 0.250 inches 0.250 inches
Body Diameter:
0.907 inches
Body Length:
3.150 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.400 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
0.017
Electrical Polarization:
Polarized
Capacitance Value Per Section:
5300.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
16.0 dc single section
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:
0.031
Case Insulation Material:
Plastic
Terminal Type And Quantity:
3 pin

N/a

Shelf Life:

NSN 5910-01-201-2249

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0