# NSN 5910-01-201-5280

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-201-5280

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not establishednot established

# **Terminal Length:**

2.500 inches 2.500 inches 2.500 inches

#### **Body Diameter:**

0.895 inches

#### **Body Length:**

Between 1.125 inches and 1.187 inches

#### **Terminal Diameter:**

0.040 inches

#### **Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

#### **Anode Type:**

Plain foil

#### **Electrical Polarization:**

Polarized

#### **Capacitance Value Per Section:**

250.000 microfarads single section

# **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

# **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Aluminum

# **Dissipation Factor At Reference Tempurature In Percent:**

2.000

# **Equivalent Series Resistance At Reference Tempurature In Ohms:**

0.80

# Dc Leakage At Reference Temp:

0.400 microamperes

#### **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

**Plastic** 

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-201-5280

Electrolytic Fixed Capacitor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0