

View Online at <https://aerobasegroup.com/nsn/5910-01-201-8580>

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 1.000 inches and 1.250 inches

Body Length:

1.400 inches

Body Width:

1.180 inches

Body Height:

1.700 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.150 inches and 0.300 inches

Center To Center Distance Between Terminals Parallel To Width:

0.590 inches

Terminal Diameter:

Between 0.030 inches and 0.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.100 inches

End Application:

Uys1 advanced signal processor, 2m/ate microminature automatic test equipment, los angeles class ssn (688), sonar, an/bsy- (v), sturgeon class ssn (637) , an/uys-1 advanced signal processor, nimitz class cvn, tarawa class lha, wasp class lhd, emory s. Land class as, forrestal class cv

Mounting Facility Type And Quantity:

2 threaded mounting studs

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

2100.000 microfarads single section

Nonderated Operating Temp:

125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Dissipation Factor At Reference Temperature In Percent:

8.0000

Special Features:

Weapon system essential

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0