

View Online at https://aerobasegroup.com/nsn/5910-01-203-1093

Body Style:
Chip type
Reliability Indicator:
Not established
Terminal Length:
0.020 inches
Body Length:
0.080 inches
Body Width:
0.050 inches
Body Height:
0.050 inches
Center To Center Distance Between Terminals Parallel To Length:
0.060 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Radio receiver r-2270/arw-83
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
1.500 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-0.50/+0.50 picofarads single section
Case Material:
Ceramic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:
Palladium and silver
Precious Material And Location:
Terminal surfaces palladium and terminal surfaces silver



Terminal Type And Quantity:

2 bonding pad

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0