

View Online at <https://aerobasegroup.com/nsn/5910-01-203-1095>

**Body Style:**

W/o mtg facilities, axial terminals/w/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established/not established

**Body Diameter:**

1.035 inches

**Body Length:**

2.843 inches

**Schematic Diagram Designator:**

Two common terminals for each electrode

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

0.029

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

9000.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

780.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

7.5 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.039

**Dc Leakage At Reference Temp:**

130.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Special Features:**

Terminals 0.060 in. Radius and diameter 0.120 in.

**Terminal Type And Quantity:**

2 uninsulated wire lead and 2 wire hook/loop

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0