

View Online at <https://aerobasegroup.com/nsn/5910-01-203-6026>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Not established

**Width Across Flats:**

Between 0.154 inches and 0.159 inches

**Terminal Length:**

0.140 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Body Length:**

0.340 inches

**Terminal Diameter:**

0.020 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

0.010 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.112 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Tolerance Range Per Section:**

-0.00/+100.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

500.0 megohms

**Power Factor At Reference Temperature In Percent:**

3.0000

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0