

View Online at <https://aerobasegroup.com/nsn/5910-01-203-8998>

**Body Style:**

W/twist tab mtg, terminal (s) on one endw/twist tab mtg, terminal(s) on one endw/twist tab mtg, terminal(s) on one end

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

0.625 inches 0.625 inches 0.625 inches

**Body Diameter:**

1.486 inches

**Body Length:**

2.046 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

500.000 microfarads single section

**Nonderated Operating Temp:**

Between -20.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+100.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

30.0000

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.78

**Dc Leakage At Reference Temp:**

95.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0