NSN 5910-01-204-0438

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-204-0438

| Body Style: |
|--|
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.250 inches |
| Body Length: |
| 0.283 inches |
| Body Width: |
| 0.276 inches |
| Body Height: |
| 0.098 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.200 inches |
| Terminal Diameter: |
| 0.019 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Internal Electrical Connection Type: |
| Extended foil |
| End Application: |
| 6625-01-079-1762 multimeter |
| Capacitance Value Per Section: |
| 0.027 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 63.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -200.0/+200.0 single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 10000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.5000 |
| Terminal Surface Treatment: |

Solder

NSN 5910-01-204-0438

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Plastic polycarbonate |
|-----------------------------|
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| NI/a |

Dielectric Material:

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0