## NSN 5910-01-204-4703

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-204-4703

	•
ROGV	Style:
Douv	Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

2.500 inches 2.500 inches 2.500 inches

**Body Diameter:** 

0.750 inches

**Body Length:** 

1.625 inches

**Terminal Diameter:** 

0.040 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

4.0

**Electrical Polarization:** 

Nonpolarized

**Capacitance Value Per Section:** 

375.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

300.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

Dc Leakage At Reference Temp:

50.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-204-4703

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0