NSN 5910-01-204-6165

Body Style:

Plastic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-204-6165

Piston
Overall Length:
0.762 inches
Terminal Length:
0.090 inches
Body Length:
0.464 inches
Overall Diameter:
0.192 inches
Center To Center Distance Between Terminals Parallel To Length:
0.414 inches
Terminal Diameter:
0.030 inches
Center To Center Distance Between Mounting Facilities Parallel To Diameter:
0.037 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.414 inches
Quality Factor At 25 Deg Celsius:
2000.0
End Application:
6625-01-079-1762 multimeter
Inclosure Type:
Encased
Terminal Location:
End opposite adjustment control perpendicular and circumference perpendicular
Adjustment Device Torque:
Between 0.200 inch-ounces and 3.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
1000000.0 megohms
Mounting Facility Type And Quantity:
3 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+0.25/+1.50 single section

Nonderated Voltage Rating And Type:

1200.0 ac rms single section or 1700.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Precious Material And Location:

External surfaces gold

NSN 5910-01-204-6165

Plastic Dielectric Variable Capacitor - Page 2 of 2



Precious Material:
Gold
Terminal Type And Quantity
3 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0