# NSN 5910-01-206-2430

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-206-2430

## **Body Style:**

W/o mtg facilities, terminal (s) on one surface

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.575 inches

## Body Length:

0.225 inches

#### **Body Width:**

0.185 inches

#### **Body Height:**

0.075 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.150 inches

#### **Terminal Diameter:**

0.010 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

3.300 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 microfarads single section

## Capacitive Electrode Material:

Tantalum

## Test Data Document:

18876-mis-20039/1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

2 uninsulated wire lead

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A010b0