NSN 5910-01-206-4431

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-206-4431

Pody Style.
Body Style:
Piston Output Longton
Overall Length:
0.495 inches
Terminal Length:
0.230 inches
Body Length:
0.457 inches
Overall Diameter:
0.140 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-75.0/+75.0 single section
Quality Factor At 25 Deg Celsius:
1500.0
Terminal Width:
0.040 inches
Terminal Thickness:
0.008 inches
Inclosure Type:
Encased
Adjustment Device Torque:
Between 0.100 inch-ounces and 2.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
1000000.0 megohms
Insulation Dc Resistance At Max Operating Temp:
100000.0 megohms
Mounting Facility Type And Quantity:
1 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Capacitance Range In Picofarads:
+0.8/+8.0 single section
Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

1 printed circuit

Terminal Type And Quantity:

NSN 5910-01-206-4431

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-c-14409/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0