NSN 5910-01-206-4431

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-206-4431

| Pody Style. |
|--|
| Body Style: |
| Piston Output Longton |
| Overall Length: |
| 0.495 inches |
| Terminal Length: |
| 0.230 inches |
| Body Length: |
| 0.457 inches |
| Overall Diameter: |
| 0.140 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| 0.0 single section |
| Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: |
| -75.0/+75.0 single section |
| Quality Factor At 25 Deg Celsius: |
| 1500.0 |
| Terminal Width: |
| 0.040 inches |
| Terminal Thickness: |
| 0.008 inches |
| Inclosure Type: |
| Encased |
| Adjustment Device Torque: |
| Between 0.100 inch-ounces and 2.000 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 1000000.0 megohms |
| Insulation Dc Resistance At Max Operating Temp: |
| 100000.0 megohms |
| Mounting Facility Type And Quantity: |
| 1 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +0.8/+8.0 single section |
| Nonderated Voltage Rating And Type: |
| 500.0 dc continuous single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Test Data Document: |
| 81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

1 printed circuit

Terminal Type And Quantity:

NSN 5910-01-206-4431

Ceramic Dielectric Variable Capacitor - Page 2 of 2



| Spec | ific | ation | Data: |
|------|------|-------|-------|
|------|------|-------|-------|

81349-mil-c-14409/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0